



QSD

ELECTRIC TRACTOR

LOAD CAPACITY:2T-35T



Horizontal QSD Tractor

LOAD CAPACITY:8T-35T



QSD series Specification List

(● Standard configuration ○ Optional × NON)

QSD	Item NO.	QSD-8	QSD-10	QSD-15	QSD-20	QSD-25	QSD-30	QSD-35
Parameter List	Towing Capability(T)	8	10	15	20	25	30	35
	Chassis	Four-wheels	Four-wheels	Four-wheels	Four-wheels	Four-wheels	Four-wheels	Four-wheels
	Dimensions	L3520× W1320	L3520× W1320	L3520× W1320	L3520× W1320	L3785× W1500	L3785× W1500	L3785× W1500
	Motor Powe (kW)	27.8	27.8	35.2	35.2	48.2	58.4	61.8
	No-load Max Speed(km/h)	≥ 12	≥ 12	≥ 12	≥ 12	≥ 12	≥ 12	≥ 12
	Full-load Max Speed(km/h)	≥ 10	≥ 10	≥ 10	≥ 10	≥ 10	≥ 10	≥ 10
	Climb Ability	8% x 15	8% x 15	8% x 15	8% x 15	8% x 15	6% x 15	6% x 15
	Towing Pin Heiht	390	390	390	390	390	390	390
	Battery Energy (Wh)	20160	23760	30240	40000	48000	57600	57600
Cab	Tire	Pneumatic tires FR.700-9/ RE.28*9-15	Pneumatic tires FR.700-9/ RE.28*9-15	Pneumatic tires FR.700-9/ RE.28*9-15	Pneumatic tires FR.700-9/ RE.28*9-15	Pneumatic tires FR.700-9/ RE.28*9-15	Pneumatic tires FR.700-9/ RE.28*9-15	Pneumatic tires FR.700-9/ RE.28*9-15
	Semi-Convertible	○	○	○	○	○	○	○
Optional Functions	Fully Enclosed Cap	○	○	○	○	○	○	○
	Lithium Battery	○	○	○	○	○	○	○
	Automatic water refilling	○	○	○	○	○	○	○
	Shock Absorbing Seat	●	●	●	●	●	●	●
	Indicator	○	○	○	○	○	○	○
	A/C	○	○	○	○	○	○	○
	Solid Tire	○	○	○	○	○	○	○

Standard Configuration



Hydraulic Steering Wheel



Shock Absorbing Seat



H/M Switch





Vertical QSD Tractor

LOAD CAPACITY:2T-15T



QSD series Specification List

(● Standard configuration ○ Optional × NON)

QSD	Item NO.	QSD-3	QSD-6	QSD-8	QSD-10	QSD-15
Parameter List	Towing capability(T)	3	6	8	10	15
	Chassis	Three-wheels	Three-wheels	Four-wheels	Four-wheels	Four-wheels
	Dimensions	L1730 × W980	L1980 × W1100	L2570 × W1280	L2570 × W1280	L2570 × W1280
	Motor Powe(kW)	11.6	16.1	20.8	27.8	35.2
	No-load Max Speed (km/h)	≥ 15	≥ 15	≥ 12	≥ 12	≥ 12
	Full-load Max Speed (km/h)	≥ 10	≥ 10	≥ 10	≥ 10	≥ 10
	Climb Ability	3% x 15	3% x 10	8% x 15	8% x 15	8% x 15
	Towing Pin Height	305/350	320/390	390/465	390/465	390/465
	Battery Energy(Wh)	11520	12960	16560	23760	31680
	Tire	Solid tire	Solid tire	Pneumatic tires FR.6.00-9/ RE.28*9-15	Pneumatic tires FR.6.00-9/ RE.28*9-15	Pneumatic tires FR.6.00-9/ RE.28*9-15
Cab	Fully-convertible	○	○	○	○	○
	Semi-convertible	○	○	○	○	○
Optional Functions	Lithium Battery	○	○	○	○	○
	Automatic Water Refilling	○	○	○	○	○
	Shock Absorbing Seat	○	○	●	●	●
	Indicator	×	×	○	○	○
	A/C	×	×	○	○	○
	Solid Tire	○	○	○	○	○

Standard Configuration



Hydraulic Steering Wheel



Shock Absorbing Seat



H/M Switch

